

Application No.: 10/792238

Case No.: 59520US002

Amendments to the Specification:

Please amend the specification as follows:

On page 30, please replace the paragraph that starts on line 25 with the word "The" and ends on page 31, line 2 with the names "(Heinecke et al.)." with the following amended paragraph:

The adhesive may optionally be a microsphere adhesive with low trauma properties as described in U.S. Pat. No. 5,614,310 (Delgado et al.); a fibrous adhesive with low trauma properties as described in U.S. Pat. No. 6,171,985 B1 (Joseph et al.); or have especially good adhesion to wet skin, such as the adhesives described in U.S. Pat. No. 6,198,016 B1 (Lucast et al.), U.S. 6,518,343 (Lucast et al.) and U.S. 6,441,092 (Gieselman) ~~and International Publication Nos. WO 99/13866 and WO 99/13865~~; multilayered adhesives as disclosed in U.S. 6,461,467 ~~Pat. Publication No. 2001/0051178 A1~~ (Blatchford et al.). A particularly preferred adhesive includes 15 wt-% acrylic acid, 15 wt-% methoxypolyethylene oxide 400 acrylate, 70 wt-% isooctyl acrylate, prepared according to Example 1 of U.S. Pat. No. 5,849,325 (Heinecke et al.).